

LG Cloud Device All-in-One Thin Client

34-inch UltraWide™ All-in-One Thin Client

34CN650N-6A



- 34-inch UltraWide™ Full HD (2560x1080) IPS Display
- Quad-core Processor (Intel® Celeron J4105)
- Adjustable Stand (Tilt, Height)
- Multi Display Setup (Up to 2 Displays with up to 4K Resolution)
- Fanless Design
- Full HD Webcam (Pop-up Type)
- Built-in Speaker



Empowered Workforce

Experience enhanced productivity and usability with the UltraWide™ Full HD resolution, 21:9 IPS display. Freely open multiple windows at once to view charts and reports side by side in high clarity. Work comfortably in a workspace with fewer cables and an adjustable monitor and stand that tilts and lifts to your personal needs.

Improved Performance

Complete tasks faster than ever with an advanced Quad-core Processor (Intel® Celeron J4105) and powerful memory capacity. It's easier stay productive with a multi-monitor set-up supporting up to 2 displays with 4K UHD resolution. This 34" UltraWide™ All-in-One is also fanless, for durability and simplified design..

Seamless Connectivity

Host online meetings and video conferences with a built-in Full HD pop-up webcam and integrated speakers. The 34CN650N-6A conveniently has multi-ports for one USB Type-C™ ports, two USB 2.0, and four USB 3.1 ports. Also, maximize productivity with Wi-Fi and Bluetooth wireless connections to work on VDIs in any environment.

34" UltraWide All-in-One Thin Client

34CN650N-6A

Specifications

| Model Name | | 34CN650N-6A |
|--------------|--------------------------------------|--|
| Display | Diagonal | 34" |
| | Aspect Ratio | 21:9 |
| | Panel Type | IPS |
| | Resolution | UltraWide™ Full HD (2560 x 1080) |
| | Brightness | 300 nits (Typ.), 240 nits (Min.) |
| | Contrast Ratio | 1,000:1 (Typ.) |
| | Response Time (GTG) ¹ | 5ms |
| | Viewing Angle (CR≥10) | 178° x 178° |
| System | Processor | Intel® Celeron J4105 (Quad Core 1.5GHz, up to 2.5GHz burst) |
| | OS | Non OS |
| | Memory | 4GB DDR4 |
| | Graphics | Integrated |
| | Storage (SSD) | 16GB eMMC |
| Connectivity | DisplayPort | 1 x DisplayPort (Output) |
| | HDMI | 1 x HDMI (Input) |
| | USB | 2x USB 2.0, 4 x USB 3.1 gen1, 1 x USB Type-C™ |
| | Mic-in | Mic-in & Headphone Out Combo |
| | Headphone Out | |
| Network | Wireless | Dual Band 802.11 a/b/g/n/ac 2x2 (BT 5.0 Combo, Internal Antenna) |
| | Bluetooth | BT5.0 |
| Sound | Built-in Stereo Speakers | 5W x 2 |
| Mechanical | Dimensions with Stand (W x H x D) | 32.5 x 22.4 x 9.0 (in) / 825.6 x 570.7 x 230 (mm) |
| | Dimensions without Stand (W x H x D) | 32.5 x 14.7 x 2.3 (in) / 825.6 x 374.8 x 60.5 (mm) |
| | Shipping Dimensions (W x H x D) | 37 x 19.3 x 9.5 (in) / 940 x 490 x 241 (mm) |
| | Weight with Stand | 18.29 lbs / 8.3kg |
| | Weight without Stand | 14.55 lbs / 6.6kg |
| | Shipping Weight | 26.5 lbs / 12.0 kg |
| | VESA | 100 x 100 (mm) |
| | Adjustable Stand | Tilt : -5° - 15°, Height Range : 100mm |
| UPC | 7 19192 64095 5 | |
| Webcam | Webcam | Yes (Pop-up Type) |
| Security | TPM | Hardware TPM 2.0 |

1) GTG: Gray to gray response time.

- <https://www.lg.com/us/business/commercial-display>
- <https://www.twitter.com/LGCommDisplays>
- <https://www.facebook.com/LGcommercialdisplays>
- <https://www.linkedin.com/company/lg-commercial-displays-usa>
- <https://www.youtube.com/lgcommercialdisplayusa>

Copyright 2020 *LG Electronics USA, Inc., 2000 Millbrook Drive Lincolnshire, IL 60069, USA.
 All rights reserved. LG and the LG logo are registered trademarks of LG Corp. All other products and brand names are trademarks or registered trademarks of their respective companies.
 Designs, features, and specifications are subject to change without notice. All screen images are simulated.
 SPEC_34CN650N-6A_082028_LR

